

## [February 2018 Latest Released Cisco 300-206 Exam Question Free Download From Lead2pass 273q

300-206 Exam Dump Free Updation Availabe In Lead2pass: <https://www.lead2pass.com/300-206.html> QUESTION 11 For which purpose is the Cisco ASA CLI command aaa authentication match used? A. Enable authentication for SSH and Telnet connections to the Cisco ASA appliance. B. Enable authentication for console connections to the Cisco ASA appliance. C. Enable authentication for connections through the Cisco ASA appliance. D. Enable authentication for IPsec VPN connections to the Cisco ASA appliance. E. Enable authentication for SSL VPN connections to the Cisco ASA appliance. F. Enable authentication for Cisco ASDM connections to the Cisco ASA appliance. Answer: C QUESTION 12 A network engineer is asked to configure NetFlow to sample one of every 100 packets on a router's fa0/0 interface. Which configuration enables sampling, assuming that NetFlow is already configured and running on the router's fa0/0 interface? A. flow-sampler-map flow1 mode random one-out-of 100 interface fas0/0 flow-sampler flow1 B. flow monitor flow1 mode random one-out-of 100 interface fas0/0 ip flow monitor flow1 C. flow-sampler-map flow1 one-out-of 100 interface fas0/0 flow-sampler flow1 D. ip flow-export source fas0/0 one-out-of 100 Answer: A QUESTION 13 What is the default log level on the Cisco Web Security Appliance? A. Trace B. Debug C. Informational D. Critical Answer: C QUESTION 14 Which command sets the source IP address of the NetFlow exports of a device? A. ip source flow-export B. ip source netflow-export C. ip flow-export source D. ip netflow-export source Answer: C QUESTION 15 Which two SNMPv3 features ensure that SNMP packets have been sent securely? Choose two. A. host authorization B. authentication C. encryption D. compression Answer: BC QUESTION 16 Which three logging methods are supported by Cisco routers? (Choose three.) A. console logging B. TACACS+ logging C. terminal logging D. syslog logging E. ACL logging F. RADIUS logging Answer: ACD QUESTION 17 Which three options are default settings for NTP parameters on a Cisco device? (Choose three.) A. NTP authentication is enabled. B. NTP authentication is disabled. C. NTP logging is enabled. D. NTP logging is disabled. E. NTP access is enabled. F. NTP access is disabled. Answer: BDE QUESTION 18 A Cisco ASA is configured for TLS proxy. When should the security appliance force remote IP phones connecting to the phone proxy through the internet to be in secured mode? A. When the Cisco Unified Communications Manager cluster is in non-secure mode B. When the Cisco Unified Communications Manager cluster is in secure mode only C. When the Cisco Unified Communications Manager is not part of a cluster D. When the Cisco ASA is configured for IPsec VPN Answer: A QUESTION 19 Which two features are supported when configuring clustering of multiple Cisco ASA appliances? (Choose two.) A. NAT B. dynamic routing C. SSL remote access VPN D. IPsec remote access VPN Answer: AB QUESTION 20 Which two device types can Cisco Prime Security Manager manage in Multiple Device mode? (Choose two.) A. Cisco ESAB. B. Cisco ASAC. C. Cisco WSAD. D. Cisco ASA CX Answer: BD **300-206 dumps full version (PDF&VCE):** <https://www.lead2pass.com/300-206.html> **Large amount of free 300-206 exam questions on Google Drive:** <https://drive.google.com/open?id=0B3Syig5i8gpDQ0xqNGttYzZGYk0> You may also need: 300-208 exam dumps: <https://drive.google.com/open?id=0B3Syig5i8gpDMXlWOHdFVkJmREU> 300-209 exam dumps: <https://drive.google.com/open?id=0B3Syig5i8gpDYnF5Vkl6OS1tc1E> 300-210 exam dumps: <https://drive.google.com/open?id=0B3Syig5i8gpDRF9kSExj1FqREU>